




## PROBLEM-SOLVING TACTICS

Below we illustrate how the above methodologies can be employed to compute the electric potential for a line of charge, a ring of charge and a uniformly charged disk.

	Charged Rod	Charged Ring	Charged disk
Figure	 <p style="text-align: center;"><b>Figure 19.49</b></p>	 <p style="text-align: center;"><b>Figure 19.50</b></p>	 <p style="text-align: center;"><b>Figure 19.51</b></p>
(2) Express dq in terms of charge density	$dq = \lambda dx'$	$dq = \lambda dl$	$dq = \sigma dA$
(3) Substitute dq into expression for dV	$dV = k_e \frac{\lambda dx'}{r}$	$dV = k_e \frac{\lambda dl}{r}$	$dV = k_e \frac{\sigma dA}{r}$
(4) Rewrite r and the differential element in terms of the appropriate coordinates	$dx'$ $r = \sqrt{x'^2 + y^2}$	$dl = R d\phi$ $r = \sqrt{R^2 + z^2}$	$dA = 2\pi r' dr'$ $r = \sqrt{r'^2 + z^2}$
(5) Rewrite dV	$dV = k_e \frac{\lambda dx'}{(x'^2 + y^2)^{1/2}}$	$dV = k_e \frac{\lambda R d\phi'}{(R^2 + z^2)^{1/2}}$	$dV = k_e \frac{2\pi\sigma r' dr'}{(r'^2 + z^2)^{1/2}}$
(6) Integrate to get V	$V = \frac{\lambda}{4\pi\epsilon_0} \int_{-\ell/2}^{\ell/2} \frac{dx'}{\sqrt{x'^2 + y^2}}$ $= \frac{\lambda}{4\pi\epsilon_0} \ln \left[ \frac{(\ell/2) + \sqrt{(\ell/2)^2 + y^2}}{-(\ell/2) + \sqrt{(\ell/2)^2 + y^2}} \right]$	$V = k_e \frac{R\lambda}{(R^2 + z^2)^{1/2}} \oint d\phi'$ $= k_e \frac{(2\pi R\lambda)}{\sqrt{R^2 + z^2}}$ $= k_e \frac{Q}{\sqrt{R^2 + z^2}}$	$V = k_e 2\pi\sigma \int_0^R \frac{r' dr'}{(r'^2 + z^2)^{1/2}}$ $= 2k_e \pi\sigma \left( \sqrt{z^2 + R^2} -  z  \right)$ $= \frac{2k_e Q}{R^2} \left( \sqrt{z^2 + R^2} -  z  \right)$
Derive E from V	$E_y = -\frac{\partial V}{\partial y}$ $= \frac{\lambda}{2\pi\epsilon_0 y} \frac{\ell/2}{\sqrt{(\ell/2)^2 + y^2}}$	$E_z = -\frac{\partial V}{\partial z} = \frac{k_e Q z}{(R^2 + z^2)^{3/2}}$	$E_z = -\frac{\partial V}{\partial z}$ $= \frac{2k_e \sigma}{R^2} \left( \frac{z}{ z } - \frac{z}{\sqrt{z^2 + R^2}} \right)$
Point-charge limit for E	$E_y \approx \frac{k_e Q}{y^2} \quad y \gg \ell$	$E_z \approx \frac{k_e Q}{z^2} \quad z \gg R$	$E_z \approx \frac{k_e Q}{z^2} \quad z \gg R$

# FORMULAE SHEET

S. No	FORMULA
1.	$q = CV$
2.	$\epsilon_0 \oint \vec{E} \cdot d\vec{A} = q.$
3.	$V_1 - V_2 = \int_1^2 \vec{E} \cdot d\vec{S}.$
4.	$V = \int_-^+ E ds = E \int_0^d ds = Ed$
5.	$q = \epsilon_0 EA.$
6.	$C = \frac{\epsilon_0 A}{d}$ (parallel-plate capacitor)
7.	$C = 2\pi\epsilon_0 \frac{L}{\ln(b/a)}$ (cylindrical capacitor)
8.	$C = 4\pi\epsilon_0 \frac{ab}{b-a}$ (spherical capacitor)
9.	$C = 4\pi\epsilon_0 R$ (isolated sphere)
10.	$C_{eq} = \sum_{j=1}^n C_j$ (n capacitors in parallel)
11.	$\frac{1}{C_{eq}} = \sum_{j=1}^n \frac{1}{C_j}$ (n capacitors in series)



S. No	FORMULA
12.	$U = \frac{1}{2}CV^2$ (potential energy)
13.	$U = \frac{q^2}{2C}$ (potential energy)
14.	$u = \frac{1}{2}\epsilon_0 E^2$ (energy density)
15.	$E = \frac{q}{4\pi K\epsilon_0 r^2}$
16.	$\epsilon_0 \oint \vec{K}E \cdot d\vec{A} = q$ (Gauss' law with dielectric).
17.	Force on a Dielectric Slab inside a Capacitor $F = \frac{\epsilon_0 bV^2 (K-1)}{2d}$



### Electric Potential Formulae

S. No	Term	Description
1	Electric Potential energy	<p><math>\Delta U = -W</math> Where <math>\Delta U =</math> Change in potential energy and <math>W =</math> Work done by the electric lines of force.</p> <p>For a system of two particles <math>U(r) = q_1 q_2 / 4\pi\epsilon r</math></p> <p>Where <math>r</math> is the separation between the charges.</p> <p>We assume <math>U</math> to be zero at infinity.</p> <p>Similarly for a system of <math>n</math> charges</p> <p><math>U =</math> Sum of potential energy of all the distinct pairs in the system</p> <p>For example for three charges</p> <p><math>U = (1 / 4\pi\epsilon)(q_1 q_2 / r_{12} + q_2 q_3 / r_{23} + q_1 q_3 / r_{13})</math></p>
2	Electric PE of a charge	$= qV$ where $V$ is the potential.
3	Electric Potential	<p>Like Electric field intensity is used to define the electric field; we can also use Electric Potential to define the field. Potential at any point <math>P</math> is equal to the work done per unit test charge by the external agent in moving the test charge from the reference point (without Change in KE)</p> <p><math>V_p = W_{ext} / q</math>. So for a point charge <math>V_0 = Q / 4\pi\epsilon r</math></p> <p>Where <math>r</math> is the distance of the point from charge.</p>

S. No	Term	Description
4.	Some points about Electric potential	<p>1. It is scalar quantity</p> <p>2. Potential at a point due to system of charges will be obtained by the summation of potential of each charge at that point</p> $V = V_1 + V_2 + V_3 + V_4$ <p>3. Electric forces are conservative force so work done by the electric force between two points is independent of the path taken</p> <p>4. <math>V_2 - V_1 = -\int E \cdot dr</math></p>
		<p>5. In Cartesian coordinates system</p> $dV = -E \cdot dr; dV = -(E_x dx + E_y dy + E_z dz)$ <p>So <math>E_x = \partial V / \partial x</math>, <math>E_y = \partial V / \partial y</math> and <math>E_z = \partial V / \partial z</math>,</p> <p>Also <math>E = \left[ \left( \partial V / \partial x \right) i + \left( \partial V / \partial y \right) j + \left( \partial V / \partial z \right) k \right]</math></p> <p>6. Surface where electric potential is same everywhere is called equipotential surface.</p> <p>Electric field components parallel to equipotential surface are always zero.</p>
5	Electric dipole	A combination of two charges +q and -q separated by a distance d has a dipole moment $p = qd$ , where d is the vector joining negative to positive charge.
6	Electric potential due to dipole	$V = (1 / 4\pi\epsilon) \times (p \cos \theta / r^2)$ <p>Where r is the distance from the center and <math>\theta</math> is angle made by the line from the axis of dipole.</p>
7	Electric field due to dipole	$E_\theta = (1 / 4\pi\epsilon) (p \sin \theta / r^3); E_r = (1 / 4\pi\epsilon) \times (2p \cos \theta / r^3)$ $\text{Total } E = \sqrt{E_\theta^2 + E_r^2} = (p / 4\pi\epsilon r^3) (\sqrt{3 \cos^2 \theta + 1})$ <p>Torque on dipole = <math>p \times E</math></p> <p>Potential Energy <math>U = -p \cdot E</math></p>
8	Few more points	<p>1. <math>\int E \cdot dl</math> over closed path is zero</p> <p>2. Electric potential in the spherical charge conductor is <math>Q / 4\pi\epsilon R</math> where R is the radius of the shell and the potential is same everywhere in the conductor.</p> <p>3. Conductor surface is a equipotential surface</p>

### Electric potential due to various charge distributions

Name/Type	Formula	Note	Graph
Point Charge	$\frac{Kq}{r}$	<ul style="list-style-type: none"> <li>q is source charge</li> <li>r is the distance of the point from the point charge.</li> </ul>	
Ring (uniform/non uniform charge distribution)	<p>At centre, <math>\frac{KQ}{R}</math></p> <p>At axis, <math>\frac{KQ}{\sqrt{R^2 + x^2}}</math></p>	<ul style="list-style-type: none"> <li>Q is source charge</li> <li>x is distance of the point from centre.</li> </ul>	

Name/Type	Formula	Note	Graph
Uniformly charged hollow conducting/ non - conducting sphere or solid conducting sphere	For $r \geq R, V = \frac{KQ}{r}$ For $r \leq R, V = \frac{KQ}{R}$	<ul style="list-style-type: none"> <li>R is radius of sphere</li> <li>r is distance of the point from centre of the sphere</li> <li>Q is total charge (<math>= \sigma 4\pi R^2</math>)</li> </ul>	
Uniformly charged solid non - conducting sphere (insulating material)	For $r \geq R, V = \frac{KQ}{r}$ For $r \leq R,$ $V = \frac{KQ(3R^2 - r^2)}{2R^3}$ $= \frac{\rho}{6\epsilon_0} (3R^2 - r^2)$	<ul style="list-style-type: none"> <li>R is radius of sphere</li> <li>r is distance of point from centre of the sphere.</li> <li>Q is total charge (<math>= \rho \frac{4}{3} \pi R^3</math>)</li> <li><math>V_{\text{centre}} = \frac{3}{2} V_{\text{surface}}</math></li> <li>Inside sphere potential varies parabolically.</li> <li>Outside potential varies hyperbolically.</li> </ul>	
Line charge	Not defined	<ul style="list-style-type: none"> <li>Absolute potential is not defined</li> <li>Potential difference between two points is given by formula <math>V_B - V_A = -2K\lambda \ln(r_B / r_A)</math>, where lambda is the charge per unit length</li> </ul>	
Infinite nonconducting thin sheet	Not defined	<ul style="list-style-type: none"> <li>Absolute potential is not defined</li> <li>Potential difference between two points is given by formula <math>V_B - V_A = -\frac{\sigma}{2\epsilon_0} (r_B - r_A)</math>, where sigma is the charge density</li> </ul>	
Infinite charged conducting thin sheet	Not defined	<ul style="list-style-type: none"> <li>Absolute potential is not defined</li> <li>Potential difference between two points is given by formula <math>V_B - V_A = -\frac{\sigma}{\epsilon_0} (r_B - r_A)</math>, where sigma is the charge density</li> </ul>	

**Electric dipole moment:**  $\vec{p} = qd\hat{z}$ , where two charges of charge  $\pm q$  are placed along the z axis at  $z = \pm \frac{d}{2}$

**Electric dipole field:** Along the z axis ( $z > d$ ):  $\vec{E} = \frac{1}{2\pi\epsilon_0} \frac{p}{|z|^3} \hat{z}$ , in the +z direction.

Along the x axis ( $x > d$ ):  $\vec{E} = \frac{1}{2\pi\epsilon_0} \frac{p}{|x|^3} \hat{x}$  in the +x direction.

Along the y axis ( $y > d$ ):  $\vec{E} = \frac{1}{2\pi\epsilon_0} \frac{p}{|y|^3} \hat{y}$  in the +y direction.